



## Specifications:

<b>Model/SKU</b>	NEMO GRABO / NG-2B-FB
<b>Battery</b>	14.8VDC 2600mAh Li-ion
<b>Rated Power</b>	16W
<b>Charger Input Voltage</b>	100-240VAC 50/60Hz
<b>Battery Charging Time</b>	~2hrs
<b>Non-Stop Running Time (Full Charge)</b>	1.5hrs
<b>Running Cycles (On Full Charge)</b>	900 ON-OFF cycles of 10 seconds
<b>Stand-by Mode (Charge Hold)</b>	30 days
<b>Pump Service Life</b>	100000+ ON-OFF cycles / 800+ hrs continuous
<b>Rated Air Flow</b>	0.7cfm ( 20 L/min )
<b>Maximum Vacuum Rate</b>	11.6Psi ( 0.8 Bar, 80 kPa )
<b>Maximum Lifting Capacity</b>	375Lbs ( 170 kg )
<b>L x W x H</b>	11.67 x 7.12 x 4.76° ( 297 x 181 x 121 mm )
<b>Net Weight (With Battery)</b>	3.3Lbs ( 1.6 kg )
<b>Working Temperature</b>	32°F~140°F ( 0°~60 °C )
<b>Applicable Surface Type</b>	Peak/valley heights less than 01° ( 3mm ), arc less than 5°

## Lifting Capacity:

Material	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry Wall
<b>Direction</b> <b>Perpendicular Hold</b> 	375Lbs ( 170 kg )	375Lbs ( 170 kg )	242Lbs ( 110 kg )	220Lbs ( 100 kg )	220Lbs ( 100 kg )	176Lbs ( 80 kg )	176Lbs ( 80 kg )	165Lbs ( 75 kg )
<b>Parallel Hold</b> 	265Lbs ( 120 kg )	265Lbs ( 120 kg )	242Lbs ( 110 kg )	220Lbs ( 100 kg )	143Lbs ( 65 kg )	176Lbs ( 80 kg )	176Lbs ( 80 kg )	143Lbs ( 65 kg )

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.

**JDPOWER PTY LTD**  
**ph: 02 42287708** [info@jdpowertools.com.au](mailto:info@jdpowertools.com.au)  
[www.jdpowertools.com.au](http://www.jdpowertools.com.au)